

MATERIAL SAFETY DATA SHEET

SECTION 1 — PRODUCT IDENTIFICATION AND USE

PRODUCT IDENTIFIER	FABRIKEM® DEGREASER & ETCH	PRODUCT IDENTIFICATION NUMBER (PIN)	1760
PRODUCT USE	Concrete cleaning compound		
MANUFACTURER'S NAME	FABRIKEM MANUFACTURING LTD.	SUPPLIER'S NAME	
STREET ADDRESS	20361 Duncan Way	STREET ADDRESS	
CITY	Langley	PROVINCE	B.C.
POSTAL CODE	V3A 7N3	EMERGENCY PHONE NO.	(604)532-3883

SECTION 2 — HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	% (W/W)	CAS NUMBER	LD ₅₀ OF INGREDIENT	LC ₅₀ OF INGREDIENT
Ethylene Glycol Monobutyl Ether	20 - 25	111-76-2	4700 mg/kg (Rat/Oral)	450 ppm (4hr./Rat)
Hydrochloric Acid	3 - 15	7647-01-0	900 mg/kg (Rat/Oral)	3124 ppm (1hr./Rat)

SECTION 3 — PHYSICAL DATA

PHYSICAL STATE	Liquid	ODOUR AND APPEARANCE	Pungent, irritating odour. Clear to light yellow coloured liquid.	ODOUR THRESHOLD (ppm)	1-35 ppm
VAPOUR PRESSURE (mm Hg) 22 @ 20°C (HC1)	VAPOUR DENSITY (AIR = 1) 1.27 (HC1)	EVAPORATION RATE (nBuAc = 1) Not Established	BOILING POINT (°C) 85.3	FREEZING POINT (°C) < 0	
pH < 1	SPECIFIC GRAVITY 1.03	COEFFICIENT OF WATER/OIL DISTRIBUTION No Data	WHMIS CLASSIFICATION	D1a; E	

SECTION 4 — FIRE AND EXPLOSION DATA

FLAMMABILITY	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> IF YES, UNDER WHAT CONDITIONS?				
MEANS OF EXTINCTION	Use media for surrounding fire and compatible with acid.				
FLASHPOINT (°C) AND METHOD	Not Applicable	UPPER FLAMMABLE LIMIT (% BY VOLUME)	Not Applicable		
AUTOIGNITION TEMPERATURE (°C)	Not Available	HAZARDOUS COMBUSTION PRODUCTS	None		
EXPLOSION DATA	SENSITIVITY TO IMPACT No		SENSITIVITY TO STATIC DISCHARGE No		

SECTION 5 — REACTIVITY DATA

CHEMICAL STABILITY	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> IF NO, UNDER WHICH CONDITIONS?				
INCOMPATIBILITY WITH OTHER SUBSTANCES	Alkalis, cyanides, sulfides, most metals, carbides, solvents.				
REACTIVITY, AND UNDER WHAT CONDITIONS	High temperatures, contact with incompatible materials. May polymerize violently with vinyl acetate.				
HAZARDOUS DECOMPOSITION MATERIALS	Toxic and corrosive gas and vapour (hydrogen chloride); hydrogen gas when in contact with metals, hydrogen cyanide and hydrogen sulphide when in contact with cyanides and sulphides.				

PRODUCT IDENTIFIER ► FABRIKEM® DEGREASER & ETCH

SECTION 6 — TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY SKIN CONTACT SKIN ABSORPTION EYE CONTACT INHALATION INGESTION

EFFECTS OF ACUTE EXPOSURE TO PRODUCT Skin and eyes: severe burns and irritation. Inhalation: coughing and choking, inflammation and ulceration of the respiratory tract, may cause pulmonary edema. Ingestion: severe internal damage, may be fatal.

EFFECTS OF CHRONIC EXPOSURE TO PRODUCT Prolonged exposure may cause erosion of teeth and chronic bronchitis. Prolonged or repeated contact to dilute solutions may cause dermatitis.

EXPOSURE LIMITS (TLV) 25 ppm on skin	IRRITANCY OF PRODUCT EYES: acute irritant. SKIN: severe irritant. INHALATION: respiratory irritant.	SENSITIZATION OF PRODUCT Not Established	CARCINOGENICITY No Data
TERATOGENICITY No Data	REPRODUCTIVE TOXICITY Not suspected	MUTAGENICITY No Data	SYNERGISTIC PRODUCTS No Data

SECTION 7 — PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT
Eye wash station and chemical safety shower.

GLOVES Impervious rubber or neoprene	RESPIRATOR Cartridge for < 50 ppm, SCBA	EYE PROTECTION Chemical Safety Goggles
FOOTWEAR Impervious rubber boots	CLOTHING Impervious, acid resistant	OTHER Accessible eye wash

ENGINEERING CONTROLS
Provide general and local exhaust ventilation to meet TLV.

LEAK AND SPILL PROCEDURE
Mop or wipe up small spills (do not allow spill to enter storm sewers or contaminate ground water). Alternative method is to dike spill area, soak up with absorbant material and dispose of in an approved manner. Vapours can be knocked down with water fog or spray.

WASTE DISPOSAL
Review all local, provincial, and federal regulations concerning health and pollution for appropriate disposal procedures.

HANDLING PROCEDURES AND EQUIPMENT
Avoid contact with eyes, skin, or clothing. Wash thoroughly after handling. When diluting, slowly add cleaner to water to avoid splattering.

STORAGE REQUIREMENTS
Store in a cool dry, well ventilated place away from incompatible substances.

SPECIAL SHIPPING INFORMATION
T.D.G. Classification: CORROSIVE LIQUID N.O.S. (CONTAINS: HYDROCHLORIC ACID AND HYDROXYACETIC ACID); CLASS 8; UN 1760; PACKING GROUP II

SECTION 8 — FIRST AID MEASURES

SPECIFIC MEASURES
EYES: Immediately flush with plenty of water for at least 15 minutes. Obtain prompt medical attention.
SKIN: Remove contaminated clothing and wash before re-use. Thoroughly flush skin with water for 15 minutes. Obtain medical attention if irritation persists.
INHALATION: Remove to fresh air. If breathing is difficult, give oxygen. Administer artificial respiration if not breathing. Obtain medical attention.
INGESTION: Do not induce vomiting. Dilute by drinking large quantities of water or milk. Obtain immediate medical attention.

SECTION 9 — PREPARATION OF MSDS

PREPARED BY W.H.M.I.S. Committee	PHONE NUMBER (604) 532-3883	DATE
-------------------------------------	--------------------------------	------