

# MATERIAL SAFETY DATA SHEET

## SECTION 1 — PRODUCT IDENTIFICATION AND USE

PRODUCT IDENTIFIER	FABRIKEM® MASONRY CLEANER TYPE L	PRODUCT IDENTIFICATION NUMBER (PIN)	1760
PRODUCT USE	Masonry cleaning compound		
MANUFACTURER'S NAME	FABRIKEM MANUFACTURING LTD.	SUPPLIER'S NAME	
STREET ADDRESS	20361 Duncan Way	STREET ADDRESS	
CITY	Langley	CITY	
PROVINCE	B.C.	PROVINCE	
POSTAL CODE	V3A 7N3	POSTAL CODE	
EMERGENCY PHONE NO.	(604) 532-3883	EMERGENCY PHONE NO.	

## SECTION 2 — HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	% (W/W)	CAS NUMBER	LD <sub>50</sub> OF INGREDIENT	LC <sub>50</sub> OF INGREDIENT
Hydrochloric Acid	25 - 35	7647-01-0	900 mg/kg (Rat/Oral)	3124 ppm (1hr./Rat)
Hydroxyacetic Acid	1 - 10	79-14-1	1950 mg/kg (Rat/Oral)	7700 ppm (4hr./Rat)

## SECTION 3 — PHYSICAL DATA

PHYSICAL STATE	Liquid	ODOUR AND APPEARANCE	Sharp, pungent, irritating odour. Amber coloured liquid.	ODOUR THRESHOLD (ppm)	1-35 ppm
VAPOUR PRESSURE (mm Hg)	22 @ 20°C	VAPOUR DENSITY (AIR = 1)	1.27 (HCl)	EVAPORATION RATE (nBuAc = 1)	Not Established
				BOILING POINT (°C)	85.3
				FREEZING POINT (°C)	-35
pH	< 1	SPECIFIC GRAVITY	1.16	COEFFICIENT OF WATER/OIL DISTRIBUTION	No Data
				WHMIS CLASSIFICATION	D1a; E

## SECTION 4 — FIRE AND EXPLOSION DATA

FLAMMABILITY	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> IF YES, UNDER WHAT CONDITIONS?			
MEANS OF EXTINCTION	Use media for surrounding fire and compatible with acid.			
FLASHPOINT (°C) AND METHOD	Not Applicable	UPPER FLAMMABLE LIMIT (% BY VOLUME)	Not Applicable	
		LOWER FLAMMABLE LIMIT (% BY VOLUME)	Not Applicable	
AUTOIGNITION TEMPERATURE (°C)	Not Available	HAZARDOUS COMBUSTION PRODUCTS	None	
EXPLOSION DATA	SENSITIVITY TO IMPACT	No	SENSITIVITY TO STATIC DISCHARGE	No

## SECTION 5 — REACTIVITY DATA

CHEMICAL STABILITY	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> IF NO, UNDER WHICH CONDITIONS?	
INCOMPATIBILITY WITH OTHER SUBSTANCES	Alkalis, cyanides, sulfides, most metals, carbides, solvents.	
	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> IF SO, WHICH ONES?	
REACTIVITY, AND UNDER WHAT CONDITIONS	High temperatures, contact with incompatible materials. May polymerize violently with vinyl acetate.	
HAZARDOUS DECOMPOSITION MATERIALS	Toxic and corrosive gas and vapour (hydrogen chloride); hydrogen gas when in contact with metals, hydrogen cyanide and hydrogen sulphide when in contact with cyanides and sulphides.	

PRODUCT IDENTIFIER ► FABRIKEM® MASONRY CLEANER TYPE L

## SECTION 6 — TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY SKIN CONTACT  SKIN ABSORPTION  EYE CONTACT  INHALATION  INGESTION

EFFECTS OF ACUTE EXPOSURE TO PRODUCT Skin and eyes: severe burns and irritation. Inhalation: coughing and choking, inflammation and ulceration of the respiratory tract, may cause pulmonary edema. Ingestion: severe internal damage, may be fatal.

EFFECTS OF CHRONIC EXPOSURE TO PRODUCT Prolonged exposure may cause erosion of teeth and chronic bronchitis. Prolonged or repeated contact to dilute solutions may cause dermatitis.

EXPOSURE LIMITS (TLV) 25 ppm on skin	IRRITANCY OF PRODUCT EYES: acute irritant. SKIN: severe irritant. INHALATION: respiratory irritant.	SENSITIZATION OF PRODUCT Not Established	CARCINOGENICITY No Data
TERATOGENICITY No Data	REPRODUCTIVE TOXICITY Not suspected	MUTAGENICITY No Data	SYNERGISTIC PRODUCTS No Data

## SECTION 7 — PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT  
Eye wash station and chemical safety shower.

GLOVES Impervious rubber or neoprene	RESPIRATOR Cartridge for < 50 ppm, SCBA	EYE PROTECTION Chemical Safety Goggles
FOOTWEAR Impervious rubber boots	CLOTHING Impervious, acid resistant	OTHER Accessible eye wash

ENGINEERING CONTROLS  
Provide general and local exhaust ventilation to meet TLV.

LEAK AND SPILL PROCEDURE  
Mop or wipe up small spills (do not allow spill to enter storm sewers or contaminate ground water). Alternative method is to dike spill area, soak up with absorbant material and dispose of in an approved manner. Vapours can be knocked down with water fog or spray.

WASTE DISPOSAL  
Review all local, provincial, and federal regulations concerning health and pollution for appropriate disposal procedures.

HANDLING PROCEDURES AND EQUIPMENT  
Avoid contact with eyes, skin, or clothing. Wash thoroughly after handling. When diluting, slowly add cleaner to water to avoid splattering.

STORAGE REQUIREMENTS  
Store in a cool dry, well ventilated place away from incompatible substances.

SPECIAL SHIPPING INFORMATION  
T.D.G. Classification: CORROSIVE LIQUID N.O.S. (CONTAINS: HYDROCHLORIC ACID AND HYDROXYACETIC ACID); CLASS 8; UN 1760; PACKING GROUP II

## SECTION 8 — FIRST AID MEASURES

SPECIFIC MEASURES  
EYES: Immediately flush with plenty of water for at least 15 minutes. Obtain prompt medical attention.

SKIN: Remove contaminated clothing and wash before re-use. Thoroughly flush skin with water for 15 minutes. Obtain medical attention if irritation persists.

INHALATION: Remove to fresh air. If breathing is difficult, give oxygen. Administer artificial respiration if not breathing. Obtain medical attention.

INGESTION: Do not induce vomiting. Dilute by drinking large quantities of water or milk. Obtain immediate medical attention.

## SECTION 9 — PREPARATION OF MSDS

PREPARED BY W.H.M.I.S. Committee	PHONE NUMBER (604) 532-3883	DATE
-------------------------------------	--------------------------------	------