

# MATERIAL SAFETY DATA SHEET

## SECTION 1 — PRODUCT IDENTIFICATION AND USE

PRODUCT IDENTIFIER	▶ FABRISHIELD® PAINT REPELLENT (PR-60; PR-61; PR-62; PR-63) and T-Series	PRODUCT IDENTIFICATION NUMBER (PIN)	
PRODUCT USE	▶ Paint Repellent Sealers		
MANUFACTURER'S NAME	FABRIKEM MANUFACTURING LTD.	SUPPLIER'S NAME	
STREET ADDRESS	20361 Duncan Way	STREET ADDRESS	
CITY	Langley	PROVINCE	B.C.
POSTAL CODE	V3A 7N3	EMERGENCY PHONE NO.	(604) 532-3883

## SECTION 2 — HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	% (W/W)	CAS NUMBER	LD <sub>50</sub> OF INGREDIENT	LC <sub>50</sub> OF INGREDIENT
Isopropanol	1-10	67-63-0	5840 mg/kg (Rats/Oral)	16,000 ppm (Rat/Inhalation/8 hr)
Ethylene Glycol Monobutyl Ether	1-5	111-76-2	470 mg/kg (Rat/Oral)	450 ppm (Rat/Inhalation/4 hr)

## SECTION 3 — PHYSICAL DATA

PHYSICAL STATE	Liquid	ODOUR AND APPEARANCE	Slight alcohol odour; pale tan liquid	ODOUR THRESHOLD (ppm)	Not Estab.
VAPOUR PRESSURE (mm Hg)	Not Available	VAPOUR DENSITY (AIR = 1)	Not Established	EVAPORATION RATE (nBuAc = 1)	> 1
pH	Not Applicable	SPECIFIC GRAVITY	0.99	BOILING POINT (°C)	83
		COEFFICIENT OF WATER/OIL DISTRIBUTION	No Data	FREEZING POINT (°C)	Not Established
		WHMIS CLASSIFICATION	B3;D2b		

## SECTION 4 — FIRE AND EXPLOSION DATA

FLAMMABILITY	▶ Vapours are flammable. Avoid sources of ignition, flame, spark, or static discharge. Empty containers may contain explosive vapours.				
MEANS OF EXTINCTION	Foam, Carbon Dioxide, Dry Chemical				
FLASHPOINT (°C) AND METHOD	70 (T.C.C.)	UPPER FLAMMABLE LIMIT (% BY VOLUME)	36.5	LOWER FLAMMABLE LIMIT (% BY VOLUME)	6.0
AUTOIGNITION TEMPERATURE (°C)	270	HAZARDOUS COMBUSTION PRODUCTS	Oxides of carbon		
EXPLOSION DATA	▶ SENSITIVITY TO IMPACT	NO	SENSITIVITY TO STATIC DISCHARGE	Yes	

## SECTION 5 — REACTIVITY DATA

CHEMICAL STABILITY	▶ Avoid sources of ignition.
INCOMPATIBILITY WITH OTHER SUBSTANCES	▶ Avoid contact with strong oxidizing agents.
REACTIVITY, AND UNDER WHAT CONDITIONS	No.
HAZARDOUS DECOMPOSITION MATERIALS	Oxides of carbon and silicon from combustion.

PRODUCT IDENTIFIER	▶ FABRISHIELD® PAINT REPELLENT (PR-60; PR-61; PR-62; PR-63) and T-Series
--------------------	--

## SECTION 6 – TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY	SKIN CONTACT <input checked="" type="checkbox"/>	SKIN ABSORPTION <input checked="" type="checkbox"/>	EYE CONTACT <input checked="" type="checkbox"/>	INHALATION <input checked="" type="checkbox"/>	INGESTION <input checked="" type="checkbox"/>
----------------	--	---	---	--	---

EFFECTS OF ACUTE EXPOSURE TO PRODUCT EYES: Moderate irritant; may cause reversible injury. SKIN: Moderate irritant; may cause dermatitis and allergic responses. INHALATION: Respiratory irritant and intoxicant; Overexposure shown by headache, dizziness and confusion to coma; material aspirated into lungs may cause chemical pneumonitis. INGESTION: May cause irritation of mouth, throat and stomach; symptoms include nausea, abdominal pain and possible collapse. **NOTE:** Pre-existing pulmonary and dermatological disorders may be aggravated by exposure to hazardous components.

EFFECTS OF CHRONIC EXPOSURE TO PRODUCT Studies suggest that solvent chronic overexposure and/or systemic toxicity effects are targeted at the kidneys and central nervous system. Repeated and prolonged skin contact may cause a pronounced sensitization effect.

EXPOSURE LIMITS (TLV) 200 ppm	IRRITANCY OF PRODUCT EYES: moderate irritant. SKIN: moderate irritant. INHALATION: respiratory irritant.	SENSITIZATION OF PRODUCT Chronic overexposure may cause sensitization.	CARCINOGENICITY No Data
TERATOGENICITY No Data	REPRODUCTIVE TOXICITY Not suspected	MUTAGENICITY No Data	SYNERGISTIC PRODUCTS No Data

## SECTION 7 – PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT  
Care should be taken to avoid inhalation of vapours and contact of product with skin or eyes.

GLOVES Impervious rubber	RESPIRATOR Organic vapour cartridge at levels above TLV.	EYE PROTECTION Chemical Safety Goggles
FOOTWEAR Impervious	CLOTHING Impervious	OTHER Accessible eye wash

ENGINEERING CONTROLS  
Use only with adequate ventilation. Local exhaust as needed to control vapour levels below recommended limits.

LEAK AND SPILL PROCEDURE  
Ventilate area. Wear appropriate protective equipment during cleanup. Eliminate sources of ignition. Shut off source of leak if safe to do so. Dike or contain spill. Absorb with inert material such as vermiculite. Sweep or shovel into containers with lids. Cover loosely and remove to appropriate waste area. Wash spill area with soap and water. Prevent washings from entering waterways.

WASTE DISPOSAL  
Review all local, provincial, and federal regulations concerning health and pollution for appropriate disposal procedures.

HANDLING PROCEDURES AND EQUIPMENT  
Tightly reseal all partially used containers.

STORAGE REQUIREMENTS  
Store away from sources of ignition.

SPECIAL SHIPPING INFORMATION  
T.D.G. Classification: Non-Regulated

## SECTION 8 – FIRST AID MEASURES

SPECIFIC MEASURES  
EYES: Flush with plenty of water for at least 15 minutes. Obtain immediate medical attention.  
SKIN: Remove contaminated clothing. Wash affected areas thoroughly with soap and water. Consult a physician.  
INHALATION: Remove to fresh air. If breathing is difficult, give oxygen. Administer artificial respiration if not breathing. Obtain medical attention.  
INGESTION: **DO NOT INDUCE VOMITING.** Give water or milk if victim is conscious and not drowsy. Should vomiting occur, be sure to keep victim's head below hips to avoid aspiration of vomitus into lungs. Obtain immediate medical attention.

## SECTION 9 – PREPARATION OF MSDS

PREPARED BY W.H.M.I.S. Committee	PHONE NUMBER (604) 532-3883	DATE
-------------------------------------	--------------------------------	------