

Fabripoint

- Cement-Based
- Non-Shrink
- Waterproof
- Pre-Mixed
- Just Add
Water

DESCRIPTION AND USE

FABRIPOINT is a cementitious, non-shrink, pre-mixed mortar especially designed for re-pointing joints in various types of masonry. It is formulated to provide a tight, waterproof joint when properly installed.

ADVANTAGES

FABRIPOINT'S non-shrink properties prevent the material from pulling away from the bond interface. Because FABRIPOINT is premixed, uniform quality as well as simplicity of mixing is ensured.

Its cement base makes FABRIPOINT totally compatible with conventional mortars and masonry.

APPLICATION

Joints should be cut out to $\frac{1}{2}$ - $\frac{3}{4}$ inches. Any loose or friable mortar should be removed before commencing re-pointing. Joints should be thoroughly flushed to remove all dust, etc. Areas to be treated should be fog misted to regulate the suction of the substrate so as to minimize premature drying of FABRIPOINT. Where excessively porous mortar is encountered, joints should be cut out an additional $\frac{3}{16}$ - $\frac{3}{8}$ inches and pre-pointed with a layer of FABRIPOINT. This will help to minimize the excessive absorption which might otherwise occur.

Mix FABRIPOINT with clean, potable water to a regular mortar consistency. Allow this mix to fatten for about twenty minutes. Remix and re-temper if necessary to desired consistency.

If added performance is required, FABRIPOINT may be mixed using FABRIBOND A (one part FABRIBOND to three parts clean water).

FABRIPOINT may require fog misting when applied in warm or windy weather to prevent too rapid drying.

Consult the manufacturer for assistance in the selection of the appropriate FABRIKEM® masonry cleaner and FABRISHIELD® water repellent treatment.

LIMITATIONS

FABRIPOINT should not be applied to frozen or frost-filled surfaces or when the temperature is below 40°F or expected to fall below 40°F within 24 hours.

Bulletin 66-B
08/'03

CAUTION

FABRIPOINT is highly alkaline and is therefore irritating to eyes and skin. Avoid contact with eyes and skin. In case of contact, thoroughly flush with large amounts of water and call physician immediately. DO NOT RUB EYES. Wash thoroughly after handling. Do not take internally. Keep out of reach of children. Keep product dry. Consult Material Safety Data Sheet before using this product.

COVERAGE

One pound of FABRIPOINT will fill approximately 17 cubic inches.

GUARANTEE

FABRIKEM MANUFACTURING LTD. guarantees its products when applied in accordance with its printed instructions. Results of inadequate surface preparation, improper mixing, incorrect application, inadequate protection, and other factors beyond the manufacturer's control cannot be held to the manufacturer's responsibility. No responsibility can be accepted beyond the purchase price of the product.

Bulletin 66-B — 08/'03

www.fabrikem.com

20361 DUNCAN WAY, LANGLEY, BC CANADA V3A 7N3
T 604-532-3883 F 604-532-3164 E info@fabrikem.com



FABRIKEM
Toll Free: 800-441-7456