

Fabritop



- Cement-Based
- Polymer Modified
- Integral Adhesive
- Pre-mixed
- Just Add Water

DESCRIPTION AND USE

FABRITOP is a polymer-modified, cementitious topping designed for spray or trowel application to concrete slabs and surfaces. Pitted, spalled, scaled, or "rained out" surfaces can be restored to a new finish.

ADVANTAGES

FABRITOP is a high strength, high density material making the product waterproof, abrasion, and freeze/thaw resistant. The inherent adhesive properties of the integral modifier give FABRITOP excellent bonding qualities.

SURFACE PREPARATION

Surfaces to be treated with FABRITOP must be clean, free of all dirt, petroleum, grease, oils, laitance, dust, form treatments, curing agents, vegetative growth, or any other foreign material. All loose, scaling, or friable concrete must be removed. Deep holes (over 1/2") should be patched with FABRIPATCH® prior to resurfacing. Areas not to be treated should be appropriately masked.

APPLICATION

Mix FABRITOP with fresh water to provide a slurry coat to be brushed onto the surface to be treated. Stiffen up the mix to a creamy consistency and trowel into place. Avoid over-wetting the mix. If feather-edging is required, mix FABRITOP with undiluted FABRIBOND-A and trowel into place.

COVERAGE

One pound of FABRITOP will fill 17 cubic inches. A 12 pound can of FABRITOP will cover 5.6 square feet at 1/4" thick. A 50 pound unit will cover 23.3 square feet at 1/4" thick. These coverages are approximate and could vary depending on site conditions, desired appearance, etc. Testing is recommended.

CAUTION

FABRITOP is highly alkaline and is therefore irritating to eyes and skin. Avoid contact with eyes and skin. In case of contact, thoroughly flush with large amounts of water and call physician immediately. DO NOT RUB EYES. Wash thoroughly after handling. Do not take internally. Keep out of reach of children. Keep product dry. Consult Material Safety Data Sheet before using this product.

Bulletin 60-B
08/'03

LIMITATIONS

FABRITOP will not repair structural defects. Care must be taken to accommodate slab movement through the use of proper control joints.

FABRITOP should not be applied when the temperature is below 5°C or expected to fall below 5°C within 12 hours of application.

Do not apply FABRITOP in layers greater than 1/2" at a time.

GUARANTEE

FABRIKEM MANUFACTURING LTD. guarantees its products when applied in accordance with its printed instructions. Results of inadequate surface preparation, improper mixing, incorrect application, inadequate protection, and other factors beyond the manufacturer's control cannot be held to the manufacturer's responsibility. No responsibility can be accepted beyond the purchase price of the product.

Bulletin 60-B — 08/03

www.fabrikem.com

20361 DUNCAN WAY, LANGLEY, BC CANADA V3A 7N3
T 604-532-3883 F 604-532-3164 E info@fabrikem.com



FABRIKEM
Toll Free: 800-441-7456